## Super Inverter Multi System Outdoor Unit

Our EASYfit split air conditioners comprises two elements - an internal and an external unit. The internal unit is fitted to a metal mounting plate on a wall in the room to be cooled, whilst the external unit is situated outside the building. The two are connected using copper pipe. The external unit, or condenser, removes the heat from the room and dissipates it outside, along with any condensation that's built-up in the system, whilst the internal unit provides cooling.





Model	KMS5MIO/X1CM
Power Rating (Ph-V-Hz)	1 / 220-240V / 50 Hz
Capacity BTU/H (cooling) kW	36000 /10.5 (12)
Capacity BTU/H (heating) kW	42000 / 12.3(14)
Power Input (W) Cooling/Heating	3280~3400(4.9)
Current Input (A) Cooling/Heating	14.6~15.3
EER (BTU/hr.w)	SEER 5.3
COP (W/W)	SCOP 3.4
Dehumidification (L/h)	N/A
Indoor Noise Level dB(A) (Hi/M/Lo)	N/A
Outdoor Noise Level dB(A)	63
Indoor Airflow (m3/h) (Hi/M/Lo)	N/A
Max. Current Rating (A) Fuse Rating (type D)	22
Net Dimension (mm) indoor (W/D/H)	N/A
Net Dimension (mm) outdoor (W/D/H)	990x345x965
Net/Gross Weight (kg) indoor	N/A
Net/Gross Weight (kg) outdoor	80
Max Room Size (m²)	N/A
Max Conservatory Size (m²) N/A	N/A
Connecting Pipe Length (m)	N/A
Pipe Diameter Liquid/Gas (Inch)	5 Sets Of 1 / 4 & 3 / 8
Selectable Temp Range °C	N/A
Minimum Operating Temp (Cooling/Heating) °C	-7 / -15
Automatic Restart after Power Failure	Yes
Automatic Refrigerant Leak Detection & Self Diagnosis Systems	Yes



## **FEATURES**

Super energy efficiency

Compact design. Only one outdoor unit.

Easy Fit, 2 Pipes system only.

Auto system restart after power failure.

Connect several indoor units to one outdoor unit.

All our systems will Heat the room as well when required.



Martin Industries Ltd

Unit 8 Milton Business Centre Wick Drive New Milton Hampshire BH25 6RH United Kingdom

Telephone: 0370 33 44 55 6 Fax: 0370 33 44 55 9

Email: info@airconditioningcentre.com Website: www.airconditioningcentre.com